


8.7/15kV THREE CORES MEDIUM VOLTAGE POWER CABLES



TECHNICAL DATA

- Max. Operating Temperature: 90°C
- Max. Short Circuit Temperature: 250°C (max. 5 sec.)
- Rated Voltage: 0,6/1kV (Um: 18.000V)
- Min. Bending Radius: 15x Cable Outer Diameter
- Production Standards: IEC 60502-1; VDE 0271; BS 5467

CONSTRUCTION

- Stranded Class 2 Copper or Aluminium Wire
- Inner layer of semi-conducting material
- XLPE Insulation
- Outer layer of semi-conducting material
- Semi-conducting tape
- Screen of copper wires
- Inner covering over laid-up cores
- Metallic Armour : Galvanised Steel Wires or Double Steel Tapes or Flat Steel Wires+ Steel Tape
- Outer sheath of Polyvinyl chloride (PVC) or Polyethylene (PE)

CODE of CABLE

- **For the Cables with Copper Conductor:**
Cu/XLPE/CTS/PVC/SWA/PVC; N2XSEYRY; N2XSEYBY;
N2XSEYGBY; N2XSEYR(FL)2Y; YXC8VZ2V-R;
YXC8VZ3V-R; YXC8VZ4V-R; YXC8VZ2(Q)2Y-R
- **For the Cables with Aluminium Conductor:**
Al/XLPE/CTS/PVC/SWA/PVC; NA2XSEYRY;
NA2XSEYBY; NA2XSEYGBY; NA2XSEYR(FL)2Y;
YAXC8VZ2V-R; YAXC8VZ3V-R; YAXC8VZ4V-R;
YXC8VZ2(Q)2Y-R

APPLICATION

These cables refer to ARMOURED Power Cables with a rated voltage of 8,7/15 kV. These are cables with low dielectric losses used in energy networks with sudden load changes. Laid in residential or industrial areas, underground in ducts and where is a risk of mechanical damage. Due to having **ARMOUR**, These cables can be used for heavy installation and mounting conditions. They are also used under normal and salty water if specially produced.

SECTION RANGE

- **For the Power Cables with Copper Conductor:**
From 35mm² up to 400mm²
- **For the Power Cables with Aluminium Conductor:**
From 35mm² up to 400mm²

SPECIAL FEATURES

- Cables can be supplied with special flame retardant PVC or Halogen Free Flame retardant(HFFR) outer sheath to comply with the flame test requirements of IEC 60332
- Category A-B and C upon special request.
- Cables can be supplied with Polyethylene outer sheath material upon special request.
- Cables can be supplied with Longitudinally or Radial+Longitudinally sealed watertight tape (Swellable tape) upon special request.
- Cables can be supplied without armour upon special request