

## UNDERFLOOR BUSBAR TRUNKING SYSTEMS



### TECHNICAL DATA

#### Current Ratings (A) :

From 63A up to 80A

Number of Conductors: 2, 3, 4 or 5

#### Structure:

- 1200 – 2400 – 3000mm optional straight lengths
- Plug-in outlets every 300mm or 600mm option
- Halogen Free plastics up to 960°C Fire rating
- Keyed Tap-off Plugs
- The springed contacts of busbar are silver plated
- On the conductor, full length isolation that provides the security of life and property against danger below which could come from outside
- Earthing continuity and installation at joint point are provided by using single bolt
- Each busbar length is complete with integral floor fixing brackets
- IP covers hinged on plug-in windows
- Clean Earth option
- Single Phase (for UPS and mains) 2 separate circuit possibilities for 2 separate busbars or for the same plug (mains, UPS)
- Addressable current reception units in different colours for the mains and UPS

Protection Standard: IP55 Protection Class

### APPLICATION

- Banks
- Business Centres
- New Generation Offices
- Hotels
- Hospitals
- Cinemas and theatres
- Conference Centres
- Educational Building
- Tourist Facilities etc
- In all kinds of buildings and alike equipped with raised floor application

### TAP-OFF UNITS

- 13A, 16A, 32A tap off plugs (with MCB or empty)
- For 32A used tap off box

