


## PE INSULATED, PVC SHEATHED OVERALL SCREENED, MULTI CORE INSTRUMENTATION CABLE



### TECHNICAL DATA

- Max. Operating Temperature: 70°C
- Rated Voltage: 300/500V
- Min. Bending Radius: 7.5x Cable Outer Diameter
- Production Standard: EN 50288-7

### CONSTRUCTION

**Conductor:** Electrolytic, stranded, annealed plain copper wires to IEC 60228 Class 2 (Class 1 or Class 5 and / or tinned on request)

**Insulation:** PE Polyethylene compound to EN 50290-2-23

**Binder Tape:** Polyester foil on overall cable core formed by stranded cores

**Collective Screen:** Aluminium/polyester foil with a tinned copper drain wire in direct contact with the metallic side of the foil

**Outer Sheath:** Flame retardant PVC compound to EN50290-2-22.

Blue for intrinsically safe cable, Black for UV resistant and/or non-intrinsically safe cable, Gray for indoor applications

### CODE of CABLE

- CU/PE/OSCR/PVC; RE-2Y(St)Y-fl (MULTICORE)

### INTRODUCTION

These cables used for connecting instruments and control systems for analogue or digital signal transmission for indoor and outdoor applications, chemistry industry, petrochemistry industry, power plants, indoors and outdoors, dry, damp and wet environments, gas stations, water conveyance systems. These cables shall not be connected directly to mains electricity supply or other low impedance sources, since they are not designed to be used for power supply.

### SECTION RANGE

- From 0.50mm<sup>2</sup> up to 2.50mm<sup>2</sup>

### CONDUCTOR QUANTITY

- From 1 core up to 50 cores

### COLOUR CODE of CABLE

- Insulation Colours code could be according to the International Standards or customer's request/demand.  
\* **Other colours can be produced upon the customer requests.**